

METSÄBOARD PRIME FBB EB (GC1)



Coated cardboard with an ecological barrier that's plastic-free and offers medium resistance to moisture and grease, high sizing, and free of optical brighteners and fluorinated chemicals. Designed for packaging takeout, fresh, dried, and frozen foods.

Printing methods

Offset
Flexography
Digital printing

Resistencia

 Microondas



Food



Food Delivery

TECHNICAL SPECIFICATIONS

WEIGHT (g/m ²) (ISO 536)	THICKNESS (mm) (ISO 534)	TABER RIGIDITY 15° (mNm) (ISO 2493)	TABER RIGIDITY 15° (mNm)
		DT	DM
195	305	3.8	7.8
210	330	4.6	9.7
220	355	5.4	11.0
230	385	6.6	13.5
245	415	8.1	16.5
265	455	10.0	20.2
280	485	11.6	23.3
320	565	15.2	28.9

PROPIEDADES

SURFACE SMOOTHNESS PPS10 (ISO 8791-4) (µm)

SURFACE WHITENESS (ISO 2470-1) (%)

ROBINSON TEST (12 months in original packaging)

Jan-23

The manufacturer of the material reserves the right to make changes without prior notice.
PEFC Chain of Custody Certificate No. CU-PEFC-COC-821792 to be able to serve this PEFC Certified material. Chain of Custody Certificate CU-COC-821792 to be able to serve this FSC certified material.